

NEW

HYGISEAT stainless steel *HYGIENE and ROBUSTESS*

Installation with Hygiseat concealed tank and carrier.

Fully AUTOMATIC!

Flush and cycle **auto-start** when user moves away.
Seat cleaning, disinfection and drying cycle start after each use.
Seat rotation **stops immediately** if the cycle is interrupted.



EXCLUSIVE

IN COLOUR

Marriage of CERAMICS and COMPOSITE MATERIALS

Thousands of combinations possible (on demand)
- RAL colour chart for HYGISEAT wall hung version
- Polyrey range for post-formed panels



For additional wash-room convenience, hygiene and cleanliness, SUPRATECH offers an extensive range of automatic ACCESSORIES : No touch taps, hand-dryers, soap dispensers, air fresheners... We also offer a wide range of accessories in STAINLESS STEEL. info@autosanit.com

1 Year Limited Guarantee - CE NORMS

Distributed by



HYGISEAT™

AUTOMATIC WC



création : imagiDée 02 47 59 25 34
Specifications subject to change without notice. Non contractual document.

NEW*

On user arrival...

4 second spray of low foam blue biological cleaning product into the WC.

* SUPRATECH Patented - Option available only for suspended ceramic HYGISEAT SUP1050 and colours SUP1070.



hygienic
intelligent
cleanliness
well designed
completely safe
minimal maintenance...

HYGISEAT™

HYGISEAT, the automatic toilet for easy use !

DOUBLE DETECTION

The intelligent WC... no manual contact



Flush and cleaning cycle start by hand movement detection
OR
Auto-start cycle after user's departure

HYGIENIC SEAT

Seat rotation cycle : clean 100 % of the time...



Washing, disinfection (Germibloc), seat dried after every use.
Seat rotation **stops immediately** if the cycle is interrupted.
Total cycle time : 12 seconds.

Seat Cleaning :
- water (at mains pressure) mixed with Germibloc disinfectant : 6 seconds.
- seat drying : 6 seconds.

GERMIBLOC

Simplified maintenance...



Cleaning, bactericide, fungicide, disinfectant, deodorizant, and biodegradable !
Germibloc™ is a product specially developed for HYGISEAT. Each time the toilet is flushed, water floods through the block releasing a GERMIBLOC dose effective against all types of micro-organisms.
Prevents lime scale formation. Lubricates all parts of the mechanism through which water flows. Eliminates the **germs** responsible for the development of **odours**.
72 g solid cylinder encased in a plastic bottle, **easy to store and handle**.
3 beeps at the end of every 1000 cycles indicates that GERMIBLOC disinfectant **requires changing**.
Fungicide to NFEN 1275 - Bactericide to NFEN 1040

NEW*

On user arrival...

4 second spray of low foam blue cleaning product into the WC.
Biological cleaning for the interior of HYGISEAT pan :
- Deodorizes and leaves a lasting fragrance, instantly eliminating the source of odours thanks to the specific action of bio-surfactants.
- Deeply cleans dirt and filth, leaving a protective film.
- Eliminates greasy and urine deposits, leaving ceramics shining like new.
- Maintains drains and U-bends clear by encouraging aerobic flora.
- Biodegradable : environmentally friendly.
Reduces dirt adherence to the ceramic.
Cleans under the seat and the upper internal edge of the bowl.

**SUPRATECH Patented - Option available only for suspended ceramic HYGISEAT SUP1050*

HYGISEAT WALL HUNG TOILET KIT

complete with mounting frame and modular post-formed stratified panels

Good looking, easy for renovation, can be installed by one person



mounting frame



panels



assembly

COLOUR OPTIONS

- RAL colour chart for HYGISEAT wall hung version
- Polyrey range for post-formed panels

Fast installation

THE DIFFERENT FLOOR-STANDING HYGISEAT VERSIONS



rear outlet



concealed (vertical) outlet



increased height

The connections are the same as for all standard ceramic toilet pans

HYGISEAT WC TOTAL SAFETY

No manual contact – 12 V power supply

- Seat rotation stops immediately if the cycle is interrupted.
- Manual flush button during power cuts.
- Electromagnetic compatibility : conforms to European EMC Directives.
- Supplied separately with each appliance : 110 - 220 / 12 V external transformer.